

CLAIM AMENDMENTS

This listing of claims will replace all prior versions and listings of claims in the application.

Listing of Claims

1. (Currently Amended) A method for reducing the power consumption in a state retaining circuit during a standby mode, comprising:

in an active state, ~~providing the state retaining circuit utilizing a regular power supply and a standby power supply to the state retaining circuit;~~

for a transition from an active state to a standby state for the purpose of reducing power consumption, while maintaining a connection to the regular power supply, decreasing the regular power supply to ground level and maintaining utilization of the standby power supply thus providing circuit elements of the state retaining circuit with enough power for retaining ~~the a~~ state during standby mode; and

for a transition from the standby state to the active state, increasing the regular power supply from ~~its the~~ ground level to ~~its an~~ active level.

2. (Currently Amended) The method of claim 1, wherein the standby power supply is decreased from ~~an the~~ active level to ~~a the~~ lower-ground level in moving from ~~an the~~ active state to ~~a the~~ standby state, the ~~lower-ground~~ level being sufficient for

retaining the state; and the standby power supply is increased from the ~~lower~~ ground level to the active level in returning back into the active mode.

3. (Currently Amended) The method of claim 2, wherein the step of decreasing the standby power supply takes place after the regular power supply has settled at a the ground level; the method further comprising the step of increasing the regular power supply to ~~an~~ the active level after the standby power supply has settled at its active level upon returning back into the active mode.

4. (Original) The method of claim 1, wherein a control signal is held during standby mode.

5. (Currently Amended) The method of claim 4, wherein said control signal is held at a predetermined ≥LOW level during standby mode.

6. (Original) The method of claim 4, wherein said control signal is held during standby mode by means external to said state retaining circuit.

7. (Previously Presented) The method of claim 4, wherein said control signal is held during standby mode by means provided within said state retaining circuit.

8. (Currently Amended) The method of claim 7, wherein said means for holding said control signal during standby mode comprises at least one transistor having a gate terminal connected to a standby signal, and arranged to be switched to an "ON" position ~~ON~~ during standby and switched to an "OFF" position ~~OFF~~ otherwise, the drain or source terminal of said transistor being connected to a line having a voltage level at which said control signal is required to be held.

9. (Original) The method of claim 8, wherein said voltage level is substantially ground.

10. (Currently Amended) The method of claim 9, wherein said transistor is an n-channel MOSFET having a gate terminal connected to a standby signal which is set "HIGH" ~~HIGH~~ during standby and LOW ~~set 'LOW'~~ otherwise, and a source terminal connected to ground.

11. (Currently Amended) A state retaining circuit, comprising:

- a control unit for providing at least one control signal;
- a data input unit for providing at least one input signal;
- a data output unit for providing at least one output signal;

a data storage unit for holding at least a part of the state of the circuit during a standby mode;

first means for coupling a power supply from a regular power supply to the circuit elements during an active mode;

second means for coupling a power supply from a standby power supply to at least a part of the data storage unit during the active mode and the standby mode;

wherein the control unit, the data input unit, the data output unit, and the data storage unit utilize both the regular power supply and the backup power supply during the active mode.

12. (Previously Presented) The circuit of claim 11, wherein the control unit is connected to the regular power supply and to the standby power supply for retaining a state of the control signal during the standby mode.

13. (Previously Presented) The circuit of claim 11, wherein the data input unit is connected to the regular power supply.

14. (Currently Amended) The circuit of claim 11, wherein the data input unit ~~(3)~~ is connected to the control signal.

15. (Previously Presented) The circuit of claim 11, wherein the data storage unit is connected to the regular power supply and to the standby power supply.

16. (Currently Amended) The circuit of claim 11, wherein the data storage unit comprises a serial circuit for retaining ~~the~~an inverted data input signal.

17. (Currently Amended) The circuit of claim 11, wherein the data output unit comprises at least one input terminal for receiving a signal from the data storage unit, and at least one output terminal for outputting the received signal from the ~~state holding~~data output unit.

18. (Original) The circuit of claim 11, wherein a selection of circuit elements of the state retaining circuit have a higher threshold voltage than circuit elements not belonging to the selection.

19. (Previously Presented) The circuit of claim 11, comprising means for holding said control signal at a predetermined level during standby.

20. (Previously Presented) The circuit of claim 19, wherein said means for holding said control signal is included in said control unit.

21. (Currently Amended) The circuit of claim 19, wherein said means for holding said control signal is connected to a standby signal which is $\geq \text{HIGH}_{\text{set}}$ "HIGH" during standby mode and $\geq \text{LOW}_{\text{set}}$ "LOW" otherwise.

22. (Currently Amended) The circuit of claim 11, including means for providing additional current to the circuit during the active mode, so as to reduce the current requirement from said standby power supply.

23. (Currently Amended) An electronic device, comprising:

- a regular power supply;
- a standby power supply;
- a first circuit portion coupled to the regular power supply;
- a second circuit portion coupled to the regular power supply, the second circuit portion comprising;

a state retaining circuit for retaining at least a part of a state of the first circuit portion during a standby mode of the electronic device, the state retaining circuit comprising:

a control unit for providing at least one control signal;

a data input unit for providing at least one input signal;

a data output unit for providing at least one output signal;

a data storage unit for holding at least a part of the state of the first circuit portion during the standby mode;

the regular power supply being arranged to supply power to the data storage unit during an active mode of the electronic device;

the standby power supply being arranged to supply power to at least a part of the data storage unit ~~(5)~~ during the active mode and the standby mode;

wherein the control unit, the data input unit, the data output unit, and the data storage unit utilize the regular power supply and the standby power supply during the active mode of the electronic device.

24. (Currently Amended) An electronic device as claimed in claim 23, wherein the standby power supply is arranged to provide a reduced power to ~~the~~ at least part of the state retaining circuit during the standby mode.

25. (Previously Presented) An electronic device as claimed in claim 23, wherein a selection of circuit elements of the state retaining circuit are located in a separate well of the second circuit portion.